

32-in. Full HD LCD Monitor



Technical Specification

System

Viewable Picture Area	31.5 in. (measured diagonally)
Aspect Ratio	16:9
Resolution	1920 x 1080 (Full HD)
Backlight	LED
Brightness/Luminance	240 cd/m ²
Contrast	1400:1
Angle of View	Horizontal: 178° Vertical: 178°
Response Time	8 ms
Display Colors	16.7 Million
Refresh Rate	60 Hz

Interface

Video Inputs	- One (1) HDMI - One (1) VGA (D-sub) - One (1) USB
Audio Output	Two (2) Built-in Speakers, 4 W

Electrical

Power Supply	100 VAC to 240 VAC (±10%), 50/60 Hz
Consumption	Standard: 55 W Standby: ≤ 0.5 W

Certifications

Safety	EN 62368-1:2014+A11:2017
Electromagnetic Compensation (EMC)	CFR 47 FCC Part 15 Subpart B EMC Directive (2014/30/EU) EN 55032:2015/AC:2016, EN55035:2017 EN 61000-3-2:2014, EN 61000-3-3:2013, EN 50130-4:2011+A1:2014

- Wide Viewing Angle
- 1080p Full HD Resolution
- High-fidelity Digital Signal Processing for Vivid Video
- Fast Response Time (8 ms) with no Image Ghosting
- Built-in Speakers
- 16.7 Million Color Display
- Supports HDMI, VGA, and USB Video Input
- Low Energy Consumption for Long Service Life



Construction/Environmental

Dimensions, without base	731.40 mm x 432.60 x 67.50 mm (28.80 in. x 17.03 in. x 2.66 in.)
Dimensions, packaging	797.0 mm x 483.0 mm x 108.0 mm (31.38 in. x 19.02 in. x 4.25 in.)
Bezel Width	13.90 mm (U/R/L), 20.50 mm (B)
Wall Mount	75.0 mm x 75.0 mm (3.0 in. x 3.0 in.)
Net Weight	3.90 kg (8.60 lb)
Gross Weight	5.10 kg (11.24 lb)
Operating Conditions	0° C to 40° C (32° F to 104° F), 20% to 85% RH

Ordering Information

Type	Part Number	Description
32 in. Monitor	DHI-LM32-F200	Full HD LCD Monitor
Package Contents	1	Monitor
	1	HDMI Cable
	1	Power Cable
	1	Pedestal
	1	Remote Control
Accessory, optional	DHL32-75-DJ	Universal VESA Bracket

Dimensions

